



Westpac Materials

Quick Identifier: Common Name (used on label and list)	Product Code:	Packaging:	Quick Identifier: Common Name (used on label and list)	Product Code:	Packaging:
Green Line	14040	50 lb bag	Lite Line 30	14025	30 lb bag
Green Line Fast Dry	14030	50 lb bag	Lite Line D-43	14035	50 lb bag
Green Line II	14135	50 lb bag	Red Line	14130	50 lb bag
Green Line II (T-19)	14125	50 lb bag	Red Line (Valencia)	14140	50 lb bag
Green Line II (Phoenix)	14145	50 lb bag	Blue Line	14100	50 lb bag
Homax	28510	50 lb bag	Blue Line (MJ)	14110	50 lb bag
Prep Coat Powder	25060	50 lb bag	Blue Line II	14180	50 lb bag
Lite Line 40	14020	42 lb bag	Black Line	14120	50 lb bag

Section 1 – Product Name & Synonyms:		“Wall Texture”	
Manufacturer’s Name	WestPac Materials, LLC.	Emergency Telephone:	714-974-6837
Street	341 W. Meats Ave.	Other Information:	
City, State, and ZIP	Orange, CA 92865	FAX:	714-637-9033
Date Prepared:	December 21, 2006	Web-Site	WestPacmaterials.com

Section 2 – Hazardous Ingredients / Identity				
<i>THE ABOVE PRODUCTS MAY CONTAIN THE FOLLOWING COMPONENTS</i>				
Hazardous Component(s) Chemical & Common name:	OSHA PEL	ACGIH TLV	% - Optional	CAS Number
Calcium Carbonate (limestone)	15 mg/m ³ ** 5 mg/m ³ *	10 mg/m ³ (e) NIC-WD		1317-65-3
1,3-Dichloropropene		4.5 mg/m ³ SKIN	< 0.00025%	542-75-6
Dichloromethane		154 mg/m ³	< 0.0003 %	
Glutaraldehyde		0.2 mg/m ³ *** SEN		111-30-8
Mica	20 mppcf ₂	3 mg/m ³ R		12001-26-2
Perlite	15 mg/m ³ ** 5 mg/m ³ *	TLV withdrawn		93763-70-3
Starch	15 mg/m ³ ** 5 mg/m ³ *	10 mg/m ³ (e)		9005-25-8
Silica - Crystalline, Quartz ₁	<u>30 mg/m³*</u> % SiO ₂ + 2 <u>10 mg/m³**</u> % SiO ₂ + 2	0.025 mg/m ³ R	~ .01 – 1.5 %	14808-60-7
Talc (containing no asbestos fibers)	20 mppcf ₂	2 mg/m ³ (e), R		14807-96-6
Titanium Dioxide	15 mg/m ³ **	10 mg/m ³		13463-67-7

341 West Meats Avenue, Orange, California 92865
Phone: (714) 974-6837 Toll Free: (866) 974-6837 FAX: (714) 637-9033

Section 2 – Hazardous Ingredients / Identity (cont.)

THE ABOVE PRODUCTS MAY CONTAIN THE FOLLOWING COMPONENTS

* Respirable fraction (PEL)
 ** Total dust (PEL) or Inhalable Particulate (TLV)
 *** STEL/CEIL – STEL stands for Short-Term Exposure Limit. Usually a 15 – minute time-weighted average (TWA) exposure that should not be exceeded at any time during a workday, even if the 8-hour TWA has not been exceeded. CEIL stands for Ceiling (C) - the concentration that shall not be exceeded during any part of the working exposure.
 NIC – TLV Notice of Intended Changes
 NIC – WD: Notice of Intended Change; Withdraw TLV
 SEN – TLV-confirmed potential for worker sensitization as a result of dermal contact and/or inhalation exposure, based on the weight of scientific evidence.
 IV – Measured as inhalable fraction and vapor
 SKIN – refers to the potential for dermal absorption of the material, including mucous membranes and the eyes either by contact with vapors or by direct skin contact

₁ - Present as a natural occurring contaminant, ACGIH Threshold limit values lists Silica-Crystalline Quartz as “A2- Suspected Human Carcinogen”
₂ - <1% crystalline silica (Quartz).
 (e) - The value is for particulate matter containing no asbestos and <1% crystalline silica.
 R – Measured as respirable fraction of the aerosol.

OTHER INGREDIENTS / IDENTITY

Hazardous Component(s) Chemical & Common name:	OSHA PEL	% - By weight (Optional)	CAS Number
VOC's	Not Established		11-30-8

SECTION 3 – PHYSICAL & CHEMICAL CHARACTERISTICS

Boiling Point	N/A	Solubility in Water	Less than 3%
Specific Gravity (H ₂ O = 1)	N/A	Reactivity in Water	N/A
Vapor Pressure (mm Hg)	N/A	pH	7 – 9
Vapor Density (Air = 1)	N/A	Melting Point	N/A
Appearance and Odor	White Powder with low odor		

SECTION 4 – FIRE & EXPLOSION DATA

Flash Point	N/A	Non-Combustible (?)	Yes
Auto-Ignition Temperature	N/A	Flammability Limits in Air (% volume)	N/A
Special Fire Fighting Procedures	None	LEL Lower	N/A
Unusual Fire and Explosion Hazards	None	UEL Upper	N/A

SECTION 5 – PHYSICAL HAZARDS (REACTIVITY DATA)

Stability	Unstable []	Stable [X]
Conditions to Avoid	None	
Incompatibility (Materials to Avoid)	Acids	
Hazardous Decomposition Products	May release CO ₂ when heated to decomposition	
Hazardous Polymerization	Will Not Occur [X]	May Occur []

341 West Meats Avenue, Orange, California 92865
 Phone: (714) 974-6837 Toll Free: (866) 974-6837 FAX: (714) 637-9033

SECTION 6 – HEALTH HAZARDS						
Acute	Inhalation of dust may cause irritation of upper respiratory system		Chronic	Long term exposure to high dust levels may impair lung function		
Signs and symptoms of Exposure			N/A			
Medical Condition Generally Aggravated by Exposure			Respiratory problems			
Chemical Listed as Carcinogen or Potential Carcinogen Y – Yes N – No or Not established P – Potential	Crystalline Silica	ACGIH TLV P - [A2]	NIOSH Yes [Ca]	NTP Yes [K]	IRAC Monograph Yes – [1]	OSHA Not specified
	Titanium Dioxide	ACGIH TLV No [A4]	NIOSH Yes [Ca]	NTP No	IRAC Monograph No - [3]	OSHA Not specified
	1,3-Dichloropropene	ACGIH TLV No [A4]	NIOSH No	NTP P	IRAC Monograph P - [2B]	OSHA Not specified
	Dichloromethane	ACGIH TLV No [A4]	NIOSH No	NTP P	IRAC Monograph P - [2B]	OSHA Not specified
Emergency and First Aid Procedures		Persons exposed to large amounts of airborne dust should leave the area to avoid the nuisance particulate material				
Routes of Entry		Inhalation	Remove to fresh air			
		Eyes	Wash with water for 15 minutes – call physician			
		Skin	Wash with soap and water			
		Ingestion	Call physician			

SECTION 7 – SPECIAL PRECAUTIONS AND SPILL / LEAK PROCEDURES	
Precautions to be taken in Handling and Storage	None
Other Precautions	None
Steps to be Taken in Case Material is Released or Spilled	Contain and Scoop materials into waste container for disposal
Waste Disposal Methods	Dispose of in accordance with all federal, state, and local regulations

SECTION 8- SPECIAL PROTECTION INFORMATION/CONTROL MEASURES			
Respiratory Protection (specify type)	NIOSH / OSHA approved respirator for dust when dry sanding. There is limited evidence that crystalline silica (quartz) causes cancer in humans.		
Ventilation	Local exhaust preferred; Mechanical Exhaust satisfactory	Special N/A	Other N/A
Protective Gloves	Yes		
Eye Protection	Safety glasses or goggles		
Other Protective Clothing or Equipment	None		
Work / Hygienic Practices	Avoid dry sanding. Wet sanding or sponging is preferred.		

341 West Meats Avenue, Orange, California 92865
Phone: (714) 974-6837 Toll Free: (866) 974-6837 FAX: (714) 637-9033

NFPA Ratings

Health: 0
Fire: 0
Reactivity: 0



HIMS Rating

Health: 0*
Fire: 0
Reactivity: 0



0 = Minimal Hazard

1 = Slight Hazard

2 = Moderate Hazard

3 = Serious Hazard

4 = Severe Hazard

The information and data herein are believed to be accurate and have been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage and handling of the product in compliance with applicable federal, state and local laws and regulations. WestPac Materials, LLC., MAKES NO WARRANTY OF ANY KIND, EXPRESSED OR IMPLIED, CONCERNING THE ACCURACY OR COMPLETENESS OF THE INFORMATION AND DATA HERIN. WestPac Materials, LLC., will not be liable for claims relating to any party's use of or reliance on information and data contained herein regardless of whether it is claimed that the information and data are inaccurate, incomplete or otherwise misleading.

341 West Meats Avenue, Orange, California 92865
Phone: (714) 974-6837 Toll Free: (866) 974-6837 FAX: (714) 637-9033